

NS42

NS42-SR20T4-3C00W
STANDARD RANGE, 2.0 MP, ESSENTIAL MV AND DL
OCR, ETHERNET WITH POE, SERIAL, USB AND
INDUSTRIAL PROTOCOLS, WHITE ILLUMINATION

- Upplösning: 2.3 Megapixel
- Pixelstorlek: 3.0 μm
- Bildhastighet: 60 fps
- Integrerad fokus och belysning
- Anomaly Detection



PRODUKTBESKRIVNING

Zebra NS42 är designad för att möta krävande tillämpningar inom industriell automation. Enheten är optimerad för robust maskinseende och integrerar kraftfulla verktyg för avvikelседetektering vid kvalitetskontroll och verifiering av monteringsmoment. NS42 stödjer även Deep learning optisk teckenigenkänning (DL-OCR), vilket möjliggör tillförlitlig och exakt avläsning av tecken – utan behov av manuell träning eller fördefinierade teckenuppsättningar.

TEKNISK DATA

Belysning	Vit
Fokus	Liquid lens
Interface out	Ethernet with POE, Serial, USB & Industrial Protocols
JavaScript-stöd	Ja
Luftfuktighet	5% to 90% RH, non-condensing
PC-utvecklingsverktyg	Aurora Focus
Pixelstorlek	3 x 3 μm
Software performance	ESSENTIAL MV AND DL OCR
Storlek	54.0 x 64.0 x 91.4 mm
Typ av scanner	Fixed Scanner
Upplösning	2.3 MP

Specifications

Recommended Services

Zebra OneCare Select™, Zebra OneCare Essential™

Decode Ranges (Typical Working Ranges)¹

NS42-SR—30° FOV Lens

Symbology/Resolution	Near	Far
5 mil Code 128	3 in./8 cm	24 in./61 cm
10 mil Code 128	3 in./8 cm	49 in./124 cm
15 mil Code 128	3 in./8 cm	70 in./178 cm
20 mil Code 128	3 in./8 cm	92 in./234 cm
5 mil DataMatrix	3 in./8 cm	13 in./33 cm
10 mil DataMatrix	3 in./8 cm	28 in./71 cm
15 mil DataMatrix	3 in./8 cm	40 in./102 cm
30 mil DataMatrix	3 in./8 cm	78 in./198 cm

NS42-WA—46° FOV Lens

Symbology/Resolution	Near	Far
5 mil Code 128	3 in./8 cm	14 in./36 cm
10 mil Code 128	3 in./8 cm	30 in./76 cm
15 mil Code 128	3 in./8 cm	42 in./107 cm
20 mil Code 128	3 in./8 cm	56 in./142 cm
5 mil DataMatrix	3 in./8 cm	8 in./20 cm
10 mil DataMatrix	3 in./8 cm	18 in./46 cm
15 mil DataMatrix	3 in./8 cm	27 in./69 cm
30 mil DataMatrix	3 in./8 cm	52 in./132 cm


Footnotes

1. Refer to Product Reference Guide for complete list of symbologies.
2. Printing resolution, contrast, power source, illumination source, and ambient light dependent.

Specifications subject to change without notice.

Connections

The device supports connections for USB-C with DisplayPort, power serial and GPIO, x-coded Ethernet, and external lighting.



- 1 External Lighting
- 2 X-Coded Ethernet Port
- 3 USB-C (with DisplayPort)
- 4 Power Serial and GPIO

Power and IO Connector




Table: Power and IO Connector Pinout Diagram

Pin	Color	Description
1	Yellow	GPIO2
2	White/Yellow	TXD
3	Brown	RXD
4	White/Brown	GPIO4
5	Violet	GPIO5
6	White/Violet	COMMON_IN
7	Red	DC_IN
8	Black	GND
9	Green	COMMON_OUT
10	Orange	GPIO6
11	Blue	GPIO1
12	Gray	GPIO3
SHELL	Bare	SHIELD

Ethernet Connector



Table: Ethernet Connector Pinout Diagram

Pin	Description
1	TP1+
2	TP1-
3	TP2+
4	TP2-
5	TP4+
6	TP4-
7	TP3-
8	TP3+
SHELL	SHIELD

External Light Connector




Table: External Light Connector Pinout Diagram

Pin	Color	Description
1	Brown	DC_OUT / GPIO8
2	White	GPIO7
3	Blue	GND
4	Black	GPIO6
5	Grey	ANALOG_OUT
SHELL	Bare	SHIELD

Specifications

Recommended Services

Zebra OneCare Select™, Zebra OneCare Essential™

Decode Ranges (Typical Working Ranges)¹

NS42-SR—30° FOV Lens

Symbology/Resolution	Near	Far
5 mil Code 128	3 in./8 cm	24 in./61 cm
10 mil Code 128	3 in./8 cm	49 in./124 cm
15 mil Code 128	3 in./8 cm	70 in./178 cm
20 mil Code 128	3 in./8 cm	92 in./234 cm
5 mil DataMatrix	3 in./8 cm	13 in./33 cm
10 mil DataMatrix	3 in./8 cm	28 in./71 cm
15 mil DataMatrix	3 in./8 cm	40 in./102 cm
30 mil DataMatrix	3 in./8 cm	78 in./198 cm

NS42-WA—46° FOV Lens

Symbology/Resolution	Near	Far
5 mil Code 128	3 in./8 cm	14 in./36 cm
10 mil Code 128	3 in./8 cm	30 in./76 cm
15 mil Code 128	3 in./8 cm	42 in./107 cm
20 mil Code 128	3 in./8 cm	56 in./142 cm
5 mil DataMatrix	3 in./8 cm	8 in./20 cm
10 mil DataMatrix	3 in./8 cm	18 in./46 cm
15 mil DataMatrix	3 in./8 cm	27 in./69 cm
30 mil DataMatrix	3 in./8 cm	52 in./132 cm


Footnotes

1. Refer to Product Reference Guide for complete list of symbologies.
2. Printing resolution, contrast, power source, illumination source, and ambient light dependent.

Specifications subject to change without notice.

Connections

The device supports connections for USB-C with DisplayPort, power serial and GPIO, x-coded Ethernet, and external lighting.



- 1 External Lighting
- 2 X-Coded Ethernet Port
- 3 USB-C (with DisplayPort)
- 4 Power Serial and GPIO

Power and IO Connector




Table: Power and IO Connector Pinout Diagram

Pin	Color	Description
1	Yellow	GPIO2
2	White/Yellow	TXD
3	Brown	RXD
4	White/Brown	GPIO4
5	Violet	GPIO5
6	White/Violet	COMMON_IN
7	Red	DC_IN
8	Black	GND
9	Green	COMMON_OUT
10	Orange	GPIO6
11	Blue	GPIO1
12	Gray	GPIO3
SHELL	Bare	SHIELD

Ethernet Connector




Table: Ethernet Connector Pinout Diagram

Pin	Description
1	TP1+
2	TP1-
3	TP2+
4	TP2-
5	TP4+
6	TP4-
7	TP3-
8	TP3+
SHELL	SHIELD

External Light Connector




Table: External Light Connector Pinout Diagram

Pin	Color	Description
1	Brown	DC_OUT / GPIO8
2	White	GPIO7
3	Blue	GND
4	Black	GPIO6
5	Grey	ANALOG_OUT
SHELL	Bare	SHIELD